

Sounder, white



Part-No. CWSO-WW-S1

Approval: G 215015

The acoustic alarm signaling device is EN 54-3 compliant, in white housing, and offers a selection of 32 signal tones including the DIN tone and other country-specific tones. All tones comply with EN 54-3. Configuration takes place via a 6-pin DIP switch. Up to two different signal tones may be activated.

Signaling device with flat base, suitable for wall and ceiling mounting.

To help define your conventional Visual Alarm Devices (VADs) requirements in line with the EN 54-23 standard, we have developed an easy to use online guide. Simply enter the room dimensions and ambient light conditions and the guide will help your device selection:

<http://www.kac.co.uk/EN54-device-chooser.htm>

Features:

- EN 54-3 compliant
- Suitable for 12 V and 24 V DC service voltage
- Synchronous sound trigger
- Volume adjustable to 2 levels at the device

Operating voltage	9 ... 29 V DC
Current consumption @ 12 V DC	approx. 14.9 mA (@ DIN tone)
Current consumption @ 24 V DC	approx. 33.4 mA (@ DIN tone)
Sound level @ 24 V DC	102.1 dB(A) (@ DIN tone)
Ambient temperature	-25 °C ... 70 °C
Type of protection	IP 21C, IP65 with CWW and accessories
Material	PC/ABS, UL94-V0
Air humidity	< 96 % (non-condensing)
Color	white, similar to RAL 9003
Weight	approx. 190 g
Specification	EN 54-3 acoustic signaling device
Dimensions	Ø: 100 mm H: 77 mm Ø: 100 mm H: 102 mm (incl. IP base)



Not suitable for use outdoors or in damp areas. Please use therefore the optional bases and accessories (Part No. CWR, PS188, PS189). Use of the deep IP socket reduces the dB output by an average of 4 dB. Replacement for Part No. 766226.

Accessories:

- CWW Base deep IP 65, white
- PS188 Base deep, O-Ring
- PS189 Base deep, seal