

SELECTABLE GALLONAGE NOZZLES

Wide-Range 369-Series Selectable Gallonage Nozzles

- 30-60-95-125-150-200 GPM (115-230-360-475-550-750 LPM)
- 100 psi (7 bar) standard, 75 psi (5 bar) optional
- Compatible with Low and Medium Expansion Foam Tube Style 214, 215 & 227 (see page 34)



Style 369

369 Wide-Range Selectable Gallonage Nozzle with Pistol Grip

369-T0 Wide-Range Selectable Gallonage Nozzle Tip Only

369-BA Wide-Range Selectable Gallonage Breakapart Nozzle

- Combination of Style 369-T0 tip and Style 102 shutoff (see page 35)



Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
369	1-1/2" (38mm)	10.2" (260mm)	5.7 (2.6kg)	30-60-95-125-150-200	115-230-360-475-550-750
369-T0	1-1/2" (38mm)	7" (178mm)	3.3 (1.5kg)	30-60-95-125-150-200	115-230-360-475-550-750
369-BA	1-1/2" (38mm)	13" (330mm)	6.2 (2.8kg)	30-60-95-125-150-200	115-230-360-475-550-750

High-Range 368-Series Selectable Gallonage Nozzles

- 95-125-150-200-250 GPM (360-475-550-750-950 LPM)
- 100 psi (7 bar) standard, 75 psi (5 bar) optional
- Compatible with Low and Medium Expansion Foam Tube Style 214, 215 & 227 (see page 34)



Style 368-T0



Style 368

368 High-Range Selectable Gallonage Nozzle with Pistol Grip

368-T0 High-Range Selectable Gallonage Nozzle Tip Only

368-BA High-Range Selectable Gallonage Breakapart Nozzle

- Combination of Style 368-T0 tip and Style 102 shutoff (see page 35)

368-BC High-Range Selectable Gallonage Nozzle with Pistol Grip

- Brass construction



Style 368-BA

368-BCTO High-Range Selectable Gallonage Nozzle Tip Only

- Brass construction

Style 368-BC

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
368	2-1/2" (65mm)	11" (280mm)	6.3 (2.8kg)	95-125-150-200-250	360-475-550-750-950
368-T0	1-1/2" (38mm)	7.1" (180mm)	3.2 (1.5kg)	95-125-150-200-250	360-475-550-750-950
368-BA	2-1/2" (65mm)	13" (330mm)	6.3 (2.8kg)	95-125-150-200-250	360-475-550-750-950
368-BC	2-1/2" (65mm)	11" (280mm)	14.7 (6.7kg)	95-125-150-200-250	360-475-550-750-950
368-BCTO	1-1/2" (38mm)	7.1" (180mm)	9.9 (4.5kg)	95-125-150-200-250	360-475-550-750-950

