

Selectable Gallongage Nozzles

Style 360-BC, 361-BC, 362-BC

- Combination pattern nozzles with versatile multiple flow settings
- Produces straight stream for maximum reach and superb wide fog pattern for optimum fire fighter protection
- Available in either lightweight hardcoat anodized aluminium or corrosion resistant brass construction
- Available in tip only and shutoff combinations
- Standard operating pressure at 100 psi (7 bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Style 360-BC and 362-BC can be used for high pressure applications up to 580 psi (40 bar) hydrostatic pressure
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Standard NH inlet or optional BIM / Machino / Storz inlets
- Optional 1-1/2" inlet size
- Compatible with Foam Style 210
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoff and Tips)



Specification

Style	Inlet Size	Length	Weigth Lbs(kg)	Flow Settings	
				GPM	LPM
360-BC	1"(25mm)	7.4"(190mm)	5.3(2.4kg)	5-10-24-40	19-37-90-150
361-BC	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	13-25-40-60	50-100-150-230
362-BC	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	12-23-30	50-90-115

Selectable Gallonnage Nozzles

Unique Features On Protek Nozzles

