

SELECTABLE GALLONAGE NOZZLES

366-BI Selectable Gallonage Nozzle with Integrated 2-1/2" Inst. Male

- BIM inlet

366-K 1-1/2" Selectable Gallonage Nozzle

- Dual fixed and spinning teeth enhance quality and efficiency of fog pattern

366-L 1-1/2" Selectable Gallonage Nozzle

- Special fluorescent bumper enables night vision search



Style 366-BI



Style 366-K



Style 366-L

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
366-BI	2-1/2" (65mm)	12.6" (320mm)	4.4 (2kg)	30-60-95-125	115-230-360-475
366-K	1-1/2" (38mm)	9" (228mm)	3.9 (1.7kg)	30-60-95-125	115-230-360-475
366-L	1-1/2" (38mm)	9" (228mm)	3.9 (1.7kg)	30-60-95-125	115-230-360-475

Mid-Range 367-Series Selectable Gallonage Nozzles

- 95-125-150-200 GPM (360-475-550-750 LPM)
- Optional 2-1/2" inlet size
- 100 psi (7 bar) standard, 75 psi (5 bar) optional
- Compatible with Low and Medium Expansion Foam Tube Style 214, 215 & 226 (see page 34)

367 Mid-Range Selectable Gallonage Nozzle with Pistol Grip

367-TO Mid-Range Selectable Gallonage Nozzle Tip Only

367-BA Mid-Range Selectable Gallonage Breakapart Nozzle

- Combination of Style 367-TO tip and Style 102 shutoff (see page 35)

367-BC Mid-Range Selectable Gallonage Nozzle with Pistol Grip

- Brass construction

367-BI Mid-Range Selectable Gallonage Nozzle with Integrated 2-1/2" Inst. Male

- BIM inlet



Style 367



Style 367-BC

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
367	1-1/2" (38mm)	10.2" (260mm)	5.7 (2.6kg)	95-125-150-200	360-475-550-750
367-TO	1-1/2" (38mm)	7.1" (180mm)	3.3 (1.5kg)	95-125-150-200	360-475-550-750
367-BA	1-1/2" (38mm)	13.1" (332mm)	6.3 (2.9kg)	95-125-150-200	360-475-550-750
367-BC	1-1/2" (38mm)	10.2" (260mm)	12.7 (5.8kg)	95-125-150-200	360-475-550-750
367-BCTO	1-1/2" (38mm)	7.1" (180mm)	8.6 (3.9kg)	95-125-150-200	360-475-550-750
367-BI	2-1/2" (65mm)	13.8" (350mm)	6.3 (2.9kg)	95-125-150-200	360-475-550-750