

INDUSTRIAL NOZZLES



- Corrosion resistant cast brass construction ideal for industrial, marine, offshore production rings and other corrosive environments
- Combination pattern nozzle with versatile multiple flow settings
- Produces straight stream for maximum reach and superb wide fog pattern for optimum fire fighter protection
- Available in tip only and shutoff combinations
- Standard operating pressure at 100 psi (7 bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Major components made from brass (UNS C83600, ASTM B62/B584) for a long-lasting service life
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)

Specification

Style	Inlet Size	Length	Weight Lbs (kg)	Flow Settings	
				GPM	LPM
366-BC	1-1/2"(38mm)	9"(228mm)	8.3(3.7kg)	30-60-95-125	115-230-360-475

INDUSTRIAL NOZZLES



Unique Features On Protek Industrial Nozzles

Unique series number
etched for easy identification



New and improved
handle design

Rrinfored metal pieces
improve durability

Stainless filter mesh
prevents blockage
caused by debris

Choice of 1-1/2" NH inlet
or 2-1/2" BIM inlet

Heavy-duty chrome
plated metal shutoff
ball for smooth action
and long life

Ergonomic design
pistol grip (available
in various colours)

Flow pattern detents
facilitate positive positioning
and smooth action

Stainless steel
spinning

Style 366-BC

Laser-etched anodized
label for excellent
durability and visibility

Large metal flow
selection ring for
enhanced grip

Raised lug for easier
pattern identification

Flush without
Changing pattern
or shutting down

Baffle etched with
pressure (psi and bar)